

Product Name : ARKIFLOOR EHG BASE
 MSDS REF NO. : 0111
 ISSUE DATE : 08.08.2025

Material Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE

PRODUCT INFORMATION

TRADE NAME : ARKIFLOOR EHG BASE
PRODUCT DESCRIPTION : TWO-COMPONENT, GLASS-FLAKES REINFORCED FLOOR COATING
COMPANY : PT. SKK KAKEN INDONESIA
ADDRESS : BEKASI INTERNATIONAL INDUSTRIAL ESTATE, BLOCK C-4, KAV. 5-7, SUKARESMI CIKARANG SELATAN, BEKASI, 17530
TEL NO. : +6221 8990 6608
EMERGENCY ASSISTANCE : AS MENTIONED ABOVE

2. HAZARD IDENTIFICATION

GHS CLASSIFICATION

Flammable Hazard	Category 2
Eye Damage/Irritation	Category 2
Skin Corrosion/Irritation	Category 2
Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 2
Carcinogenicity	Category 2

GHS LABEL ELEMENT



Signal Word Danger

Hazardous Information

- Flammable liquid and vapor
- Causes skin irritation
- May cause an allergic skin reaction
- Causes serious eye irritation
- May cause genetic defects
- May cause cancer

Precautionary Statements

«Prevention»

- Obtain special instructions before use

Product Name : ARKIFLOOR EHG BASE
MSDS REF NO. : 0111
ISSUE DATE : 08.08.2025

- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surface.
- Keep container tightly closed.
- Ground/bond container and receiving equipment, use only non-sparking tools.
- Use explosion-proof electrical/ventilating/lightning equipment.
- Take precautionary measures against static discharge.
- Avoid breathing dust/fumes/gas/mist/spray/vapors.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing should not be allowed out of the workplace.
- Use personal protective equipment as required.
- Wear protective gloves/protective clothing/eye protection/face protection as required.

«First Aid Measures»

- IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If on SKIN : Remove immediately all contaminated clothing. Wash with soap and water. Rinse skin with water/shower.
- If skin irritation or a rash occurs : Get medical advice/attention.
- If eye irritation persists : Get medical advice/attention.
- If exposed or concerned : Get medical advice/attention.
- In case of fire : Use appropriate media for extinction.
- Take off all contaminated clothing and wash before reuse.
- Get medical advice/attention if you feel unwell.

«Storage»

- Keep container tightly closed. Store locked up.
- Store in a well ventilated place. Keep cool.

«Disposal»

- Dispose of contents and container to appropriate waste site in accordance with local and national regulation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NO.	CONC.
Bisphenol-A type solid epoxy resin	25036-25-3	20 – 35 %
Xylene	1330-20-7	5 – 8 %

4. FIRST AID MEASURES

Inhalation

Move person to fresh air and call for medical assistance immediately. If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

Product Name	: ARKIFLOOR EHG BASE
MSDS REF NO.	: 0111
ISSUE DATE	: 08.08.2025

Skin Contact

Wash skin with mild soap and large amounts of water immediately. Remove all contaminated clothes and shoes. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

Eye contact

In case of eye contact, immediately flush eye with large amounts of clean water until irritation subsides. Remove contact lens. Get medical attention if irritation persists.

Ingestion

Do not induce vomiting. Rinse mouth with plenty of water. Get immediate medical advice/attention immediately.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA : Dry Chemical, Alcohol-resistant foam, CO₂.

FIRE FIGHTING PROCEDURE : Flammable liquid and vapors
Use water spray to cool fire-exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours. Avoid spraying water directly into storage containers. Closed containers may explode when exposed to extreme heat. Avoid spreading burning liquid with water, isolate liquid. Do not allow runoff from fire fighting to enter drains or watercourses. If possible, isolate product from heat, electrical equipment, sparks and open flame.

FIRE FIGHTING EQUIPMENT : Fire-fighters should use protective clothing, eyes protection, and self-contained breathing apparatus. Respiratory & eye protection required for fire-fighting personnel. Full protective equipment and self-contained breathing apparatus (SCBA) should be. Used for all indoor fires and any significant outdoor fires.

HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS : Carbon dioxides and Carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Avoid contact with spilled material. Avoid product contact with eye. Do not inhale vapours. Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes. Ensure supply of fresh air in enclosed rooms.

ENVIRONMENTAL PRECAUTIONS:

Prevent further leakage or spillage if safe to do so. Discharge into the environment must be avoided. Do not let product enter drains. Do not flush into surface water of sanitary sewer system. Collect contaminated fire extinguishing water separately, this must not be discharged into drains. Advise authorities if product has entered a watercourse or sewer.

Product Name : ARKIFLOOR EHG BASE
MSDS REF NO. : 0111
ISSUE DATE : 08.08.2025

CLEAN-UP-METHODS:

Transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely.

7. HANDLING AND STORAGE**HANDLING**

Avoid breathing mist or vapors. Avoid contact with skin. Use non-sparking tools and explosion proof equipment. Use only with adequate ventilation. Use proper bonding and/or earthing procedures. Prevent small spills and leakage to avoid slip hazard.

STORAGE

Keep containers tightly closed. Store in a cool, dry and well - ventilated place and accordance with local regulations. Keep away from incompatible materials, ignition sources and do not smoke. Keep out of the reach of children. Protect containers against physical damage and check regularly for leaks.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**CONTROL PARAMETERS / OCCUPATIONAL LIMITS**

Substances	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m ³	ppm	mg/m ³
Bisphenol-A type solid epoxy resin	-	-	-	-
Xylene	100	434.00	-	-

ENGINEERING CONTROLS

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.

Ensure eyewash stations and safety showers are close to the workstation location.

PERSONAL PROTECTIVE EQUIPMENT

For respiratory organs : Wear suitable breathing apparatus is recommended.

For eyes : Wear chemical safety goggles with side shield is recommended.

For skin and body : Wear chemical resistant clothes, safety gloves and safety shoes when handling the product. Wash hands with soap and water after handling.

For protection clothing : Wear safety helmet, full protective clothing, safety shoes.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM : Liquid

COLOUR : Depends on specified colour

Product Name	: ARKIFLOOR EHG BASE
MSDS REF NO.	: 0111
ISSUE DATE	: 08.08.2025

ODOR : Characteristic

BOILING POINT : 137 – 143 °C

MELTING/FREEZING POINT: No Data available

FLASH POINT : 20 °C (Closed Cup)

SPECIFIC GRAVITY : 1.22 ± 0.10 (depends on colour)

FLAMMABILITY LIMIT : 1.1 – 11.2 % by vol.

VAPOUR PRESSURE : No Data Available

AUTOIGNITION TEMP. : >230 °C

10. STABILITY AND REACTIVITY

REACTIVITY

No dangerous reaction known under condition of normal use.

STABILITY

Stable under ordinary conditions of use and storage.

HAZARDOUS REACTIONS

Under normal conditions of storage and use, hazardous reaction will not occur.

CONDITION TO AVOID

Heat, open flame and other ignition sources.

INCOMPATIBLE MATERIALS

Oxidizing agents, strongly alkaline and strongly acid materials.

HAZARDOUS DECOMPOSITION PRODUCTS

Smoke / carbon dioxide / carbon monoxide / oxides of nitrogen.

11. TOXOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

Acute Oral toxicity

Harmful if swallowed

<u>Substances</u>	<u>Oral LD50 (Rat), mg/kg</u>
Bisphenol-A type solid epoxy resin	2001
Xylene	4300

Product Name	: ARKIFLOOR EHG BASE
MSDS REF NO.	: 0111
ISSUE DATE	: 08.08.2025

Acute dermal/skin toxicity

May caused skin Irritation if in contact with skin

<u>Substances</u>	<u>Dermal LD50 (Rabbit), mg/kg</u>
Bisphenol-A type solid epoxy resin	2001
Xylene	1700

Acute inhalation toxicity

May caused irritating to eyes and respiratory tract if inhaled

<u>Substances</u>	<u>Inhalation vapor LC50 (Rat), mg/L/4hr</u>
Bisphenol-A type solid epoxy resin	Data not available
Xylene	5000

Skin Corrosion or Irritation

May cause skin irritation

Serious eye damage or Irritation

May be an eye irritant

Respiratory or skin sensitisation

May be irritating to eyes and respiratory tract

Germ cell mutagenicity

No information available on the product

Carcinogenicity

Titanium Dioxide

Titanium Dioxide is being classified by The International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). This is being based on inadequate evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

Reproductive Toxicity

No information available on the product

Specific Target Organ Toxicity (STOT)- Single Exposure

No information available on the product

Specific Target Organ Toxicity (STOT)- Repeated Exposure

No information available on the product

Product Name	: ARKIFLOOR EHG BASE
MSDS REF NO.	: 0111
ISSUE DATE	: 08.08.2025

Asphyxiation hazard

No information available on the product

12. ECOLOGICAL INFORMATION

There is no data available on the product itself. The product should not be allowed to enter drains or watercourses or to be deposited where it can affect ground or surface waters.

13. DISPOSAL INFORMATION

Recycle wherever possible. Consult manufacturer for recycling options. Do not dispose into the environment, in drains or in water courses. Method of waste disposal are incineration or biological treatment in state/federal approved facility and must be accordance with local waste and environmental authority requirements. Empty containers should be recycled or disposed through an approved waste licensed contractor.

14. TRANSPORT INFORMATION**LAND TRANSPORT ADR,RID**

Class	3
Packaging Group	III
UN NO.	1263
Shipping Name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

SEA TRANSPORT IMDG

Class	3
Packaging Group	III
UN NO.	1263
MARINE POLLUTANT	No
Shipping Name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

AIR TRANSPORT ICAO/IATA

Class	3
Packaging Group	III
UN NO.	1263
Shipping Name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Product Name	: ARKIFLOOR EHG BASE
MSDS REF NO.	: 0111
ISSUE DATE	: 08.08.2025

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this product.

Applicable national regulations:

Standard on hazard communication for hazardous chemicals and dangerous goods

SS-586: Part 1: 2014- Transport and storage of dangerous goods

SS-586: Part 2 :2014 – GHS of classification and labelling of chemicals

SS-586: Part 3: 2008(2014)- Preparation of safety data sheet

MOM : Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations

NEA: Environmental Protection and Management Act & Environmental Protection and management (Hazardous Substances) Regulations

SCDF : Fire Safety Act & Fire Safety(Petroleum and Flammable Materials) Regulations

SPF : The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules

16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate and the source of information which we have obtained is believed to be reliable. However, we cannot assume any liability whatsoever for the accuracy or completeness of the information contained herein. Due to the conditions of handling, storage, use and disposal of this product are beyond our control, we shall not be liable for any damages incurred by the use of this product. All materials may present unknown hazards and should be used with caution. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.